

FIRST FOR THE FUTURE

Filtertechnik DFU-2 Fuel Polishing System:

Next Generation efficiency, the ultimate in fuel cleanliness performance enhanced!



BEFORE & AFTER

Filtertechnik's market leading DFU-2 is the complete solution for fuel contamination. Offering an increased capacity and a variety of additional options, the DFU-2 provides absolute assurance that your fuel is clean, dry and ready for use.

Extensively specified into:

- Plant Equipment Hire
- Mining/Quarrying
- Healthcare
- Marine
- Telecommunications
- Rail
- Broadcasting and Media

THE NEXT GENERATION

Introduction

The DFU-2 is the more powerful version of our entry level DFU-1, offering increased capacity and a range of enhanced options. High capacity particulate filtration principals are again expertly incorporated to ensure removal of solid and bacterial contamination down to 18/16/13 or better. Water is also removed with the unparalleled performance of Filtasorb2 cells, removing all free water and 99.9% of entrained water to an incredible 100ppm or less.

Whilst capacity is increased in the DFU-2, the system still remains within a compact footprint ensuring it is fully portable, easy to manoeuvre and will work in almost any setting.

A full range of additional options are also available on the DFU-2. Particle counters can be included for analysis, as well as bacterial fuel conditioners, flow meters and more. Whatever your application, we have an option to ensure your system is fully compliant to industry specifications. Should on-site verification of cleanliness levels be required, practical quick connect fittings allow for instant plug-in to the Particle Pal fuel cleanliness analyser, allowing real time results in ISO/NAS/SAE in a matter of minutes.

FEATURES

- Lightweight and portable, perfect for mobile use and basement tank access
- Powerful pump with high flow rates up to 90 L/min
- High volume dirt holding capacity to deliver ISO cleanliness codes of 18/16/13 or better
- High performance Filtasorb2 inserts to achieve 100ppm or better
- Extensive selection of filter cell inserts to suit every clean-up application
- Pressure gauge indication of system performance
- Water drain valve on sump of filter housing
- Rugged frame with integral drip tray
- All terrain pneumatic wheels
- A range of optional extras available, including particle counters, flow meters and fuel conditioners
- Suitable for most diesel, kerosene, biodiesel (B100) and oil applications



BENEFITS

- Clean, dry fuel, ready for use when required
- Recover and re-use contaminated fuels
- Low running costs
- Can be moved between tanks or dedicated to a single tank
- Single pass cleanliness
- Ideal for tank cleaning and fuel recovery



CONNECT TO YOUR PARTICLE PAL
FOR REAL TIME CLEANLINESS,
TRENDING AND ARCHIVE CREATION

Filtasorb²
Next generation
Water absorbent filtration media





UK MANUFACTURED

SPECIFIED INTERNATIONALLY



DFU-2 TECHNICAL SPECIFICATION

Model	DFU-2-110 / DFU-2-240	
Dimensions	610 mm (W) 690 (D) 1260 (H)	
Flow Rate	90 L/min	
Dry weight	95 Kg	
Frame	Mild Steel	
Finish	Powder coated	
Voltage	110 VAC +10%/-6%	(DFU-2-110)
	230 VAC +10%/-6%	(DFU-2-240)
Frequency	50 Hz ±2%	
Current	6 Amps	
Switch	Overload contactor	
Power	1.5 KW	
Overload	4-11 Amp	
Starter contractor	Yes	
Pump	Self priming vane type	
Duty Cycle	Continuous	
Noise Level	<70dB @ 1 meter	
Motor Protection	Thermal overload protection	
Filtration	Filter cell for particulate & solid contamination removal to 18/16/13 or better. Water removal with Filtasorb2 to under 100ppm. Optional magnets to pick up rust.	
Bypass (Pump)	Cracking 26 psi (1.8 bar)	
	Full Flow 32 psi (2.2 bar)	
Filter Indicator	Dual Mechanical pressure differential	
Pressure	10 bar max	
Temperature	-5 - +55°C max	
Medium	Diesel	
Environment	IP55	
Connections	1" BSP Ball valves	

CALL US FIRST AND REQUEST MORE INFORMATION ABOUT
OUR ENTIRE RANGE OF THE DFU FAMILY
FREEPHONE 0800 0087 456 OR EMAIL sales@filtertechnik.co.uk



Filtertechnik

Filtertechnik Ltd, 1 Central Park, Lenton Lane, Nottingham, NG7 2NR

Tel: +44 (0) 115 9003 600 Fax: +44 (0) 115 9868 875

Free Phone: 0800 0087 456 Email: sales@filtertechnik.co.uk

www.filtertechnik.co.uk